



Hard nylon threaded hex head bungs Strong and durable

SPECIAL FEATURES

- Thick wall that can be drilled and tapped
- Reduce from large holes to small holes with minimum protrusion
- No slots or recesses to collect dirt
- Excellent mechanical properties

Metric

Thread	OD mm	FL mm	W mm	Sold Each	Cat No
M12 x 1.5	12	8	18	1	HB12
M16 x 1.5	16	10	18	1	HB16
M20 x 1.5	20	10	24	1	HB20
M25 x 1.5	25	12	30	1	HB25
M32 x 1.5	32	12	36	1	HB32
M40 x 1.5	40	12	43	1	HB40
M50 x 1.5	50	12	53	1	HB50
M63 x 1.5	63	12	69	1	HB63

Pg

Thread	OD mm	FL mm	W mm	Sold Each	Cat No.
Pg9	15.2	8	18	1	HBPG09
Pg11	18.6	10	22	1	HBPG11
Pg13.5	20.4	10	24	1	HBPG13
Pg16	22.5	10	27	1	HBPG16
Pg21	28.3	12	36	1	HBPG21
Pg29	37.0	12	43	1	HBPG29
Pg36	47.0	12	53	1	HBPG36

TECHNICAL DATA

Material: Nylon
Colour: Metric—Black or Grey/PG—Black Only
Working temp: -40°C to 100°C. Short term 130°C
Chemical resistance: Excellent resistance to oils, petrol, alcohols, seawater, caustic soda, weak acids, alkalis, bases and salts.

Additional technical information available on request

Dimensions and specifications may be changed without notice.

A product designed and distributed by

McCABE INDUSTRIES LTD

667C High Street, Lower Hutt 5010, New Zealand
 Ph: 045289619; Email: info@mccabeindustries.co.nz
 www.mccabeindustries.co.nz



Made in New Zealand