

HEX BUNGS

Metric/Pg






Hard nylon threaded hex head bungs Strong and durable




SPECIAL FEATURES

- Thick wall that can be drilled and tapped
- Reduce from large holes to small holes with minimum protrusion
- No slots or recesses to collect dirt
- Excellent mechanical properties

Metric

| Thread |  mm |  mm |  mm | Pack size | Cat No |
|-----------|---|---|---|-----------|--------|
| M12 x 1.5 | 12 | 8 | 18 | 50 | HB12 |
| M16 x 1.5 | 16 | 10 | 18 | 50 | HB16 |
| M20 x 1.5 | 20 | 12 | 24 | 50 | HB20 |
| M25 x 1.5 | 25 | 12 | 30 | 25 | HB25 |
| M32 x 1.5 | 32 | 12 | 36 | 25 | HB32 |
| M40 x 1.5 | 40 | 12 | 43 | 10 | HB40 |
| M50 x 1.5 | 50 | 12 | 53 | 5 | HB50 |
| M63 x 1.5 | 63 | 12 | 69 | 5 | HB63 |

Pg

| Thread |  mm |  mm |  mm | Pack size | Cat No. |
|--------|--|---|---|-----------|---------|
| Pg9 | 15.2 | 8 | 18 | 10 | HBPG09 |
| Pg11 | 18.6 | 10 | 22 | 10 | HBPG11 |
| Pg13.5 | 20.4 | 10 | 24 | 10 | HBPG13 |
| Pg16 | 22.5 | 10 | 27 | 10 | HBPG16 |
| Pg21 | 28.3 | 12 | 36 | 5 | HBPG21 |
| Pg29 | 37.0 | 12 | 43 | 5 | HBPG29 |
| Pg36 | 47.0 | 12 | 53 | 5 | HBPG36 |
| | | | | | |
| | | | | | |

TECHNICAL DATA

- Material:** Nylon
Colour: Metric—Black or Grey/Pg—Black Only
Working temp: -40°C to 100°C. Short term 130°C
Chemical resistance: Excellent resistance to oils, petrol, alcohols, seawater, caustic soda, weak acids, alkalis, bases and salts.

Additional technical information available on request

Dimensions and specifications may be changed without notice.

A product designed and distributed by

McCABE INDUSTRIES LTD

667C High Street, Lower Hutt 5010, New Zealand
Ph: 045289619; Email: info@mccabeindustries.co.nz
www.mccabeindustries.co.nz



Made in New Zealand