

# CABLEMATE

## PLASTIC CABLE GLAND

Supplied complete with locknut




**IP68 Protection at 5 bar (72 psi)**

50 metres submersible

### FEATURES

- The range covers cables from outside diameters of 2.5 mm to 54 mm
- Integral claw type cable grip
- Nut will not thread bounce
- Low profile above mounting surface

ALSO AVAILABLE WITH WAVE SEAL™ IP68 SURFACE MOUNTING SEALING WASHER

| Cat No. | Thread size | Thread Length |  | Cable Range OD | Pack size |
|---------|-------------|---------------|---|----------------|-----------|
| GX12    | M12 x 1.5   | 10            | 15  | 2.5 - 6        | 50        |
| GX16    | M16 x 1.5   | 15            | 22  | 4.5 - 10.2     | 50        |
| GX20    | M20 x 1.5   | 15            | 27  | 7.5 - 13.2     | 50        |
| GX25    | M25 x 1.5   | 15            | 32  | 13 - 18        | 25        |
| GX32    | M32 x 1.5   | 15            | 42  | 17.5 - 25      | 20        |
| GX40    | M40 x 1.5   | 15            | 51  | 24.5 - 31.5    | 5         |
| GX50    | M50 x 1.5   | 15            | 65  | 31 - 43        | 2         |
| GX63    | M63 x 1.5   | 18            | 80  | 43 - 54        | 2         |

### TECHNICAL DATA

**Material:** Nylon

**Colour:** Black or Grey

**Working temp:** -40°C to 100°C  
Short term 130°C

**Chemical resistance:**  
Excellent resistance to oils, petrol, alcohols, seawater, caustic soda, weak acids, alkalis bases and salts.

Additional technical information available on request

Dimensions and specifications may be changed without notice.



A product designed and distributed by

**McCABE INDUSTRIES LTD**

667C High Street, Lower Hutt, New Zealand

Ph: 04 5289619; Email: [info@mccabeindustries.co.nz](mailto:info@mccabeindustries.co.nz)

[www.mccabeindustries.co.nz](http://www.mccabeindustries.co.nz)